







HI 991300 and HI 991301

pH/EC/TDS MULTIPARAMETER METERS

HI 991300 and HI 991301 have been designed to offer you pH, electrolytic-conductivity, total dissolved solids and temperature measurements all in a slim, lightweight, portable unit. For greater precision in your application, both models are available, each with different conductivity ranges. From purified to brine waters, just choose the model for your range of measurement.

The HI 1288 pre-amplified multiparameter probe features an easy to clean flat tip sensor and a cloth junction that can be pulled longer to increase the life of the probe.

User selectable features include different TDS factors from 0.45 to 1.00, and a range of temperature coefficients (B) from 0.0 to 2.4% for greater consistency and reproducibility.

These instruments easily fit in the palm of your hand and the bottom probe connection ensures the electrode cable doesn't get in your way. The large, multi-level LCD displays the primary reading, temperature and calibration guides simultaneously.

FEATURES

- Waterproof to IP 67
- Multi-level LCD display

The meters display the current measurement simultaneously with the current temperature. A quickguide is also displayed to aid users in instrument operation.

HOLD

The Hold button freezes readings on the display for manual recording.

 Automatic Temperature Compensation

- Automatic 1 or 2 point calibration
- BEPS

BEPS (Battery Error Prevention System) alerts the user in the event that low battery power could adversely affect readings.

- Battery % displayed on startup.
- Heavy-duty

The enclosure of these waterproof meters are made of tough ABS plastic for harsh environments.

· Easy to clean and keep clean



B.E.P.S. +
Battery Error
Prevention System



ISO 9001:2000 CERTIFIED

WE DESIGN, MANUFACTURE, SUPPLY AND SUPPORT ALL OF OUR PRODUCTS.

THAT'S 360° VALUE

Over the past 30 years, **HANNA** has never failed to design fresh and innovative products and the new HI 991300 and HI 991301 are no exception. We are excited to introduce such high accuracy and ease of use in a compact, modern design that fits right in your hand.

HANNA is the largest family-owned manufacturer of analytical instrumentation in the world. The HI 991300 and HI 991301 are manufactured in our European state-of-the-art ISO 9001:2000 production facility and is CE compliant to EN 61326-1 and EN 61010-1 standards.

When you buy a **HANNA** product, you're not only buying the best value for your money, but you're also adding the benefit of **HANNA**'s unsurpassed customer service and post-sale technical support.

Multiparameter Probe & Starter Solutions Included!











HI 1288 MULTIPARAMETER PROBE

The HI 1288 multiparameter probe includes pH, EC/TDS and temperature measurement in one convenient, rugged handle. A solid-state pre-amplifier is integrated into the probe to ensure against interference from transient electrical noise.



• Extendable Cloth Junction

The HI 1288 multiparameter probe features a cloth junction that can be pulled longer, effectively increasing the life of the probe.

Easy to Clean

The flat tip sensor is easy to clean and keep clean by design.

SPECIFICATIONS		НІ 991300	HI 991301	
	рН	0 to 14.00 pH		
Range	EC	0 to 3999 μS/cm	0.00 to 20.00 mS/cm	
	TDS	0 to 2000 ppm (mg/L)	0.00 to 10.00 ppt (g/L)	
	Temp.	0.0 to 60.0°C/32.0 to 140.0°F		
Resolution	рН	0.01 pH		
	EC	1 μS/cm	0.01 mS/cm	
	TDS	1 ppm (mg/L)	0.01 ppt (g/L)	
	Temp.	0.01°C/0.1°F		
Accuracy (@20°C)	рН	±0.01 pH		
	EC/TDS	±2% F.S.		
	Temp.	±0.5°C/±1°F		
Temperature	pH Automatic		utomatic	
Compensation	EC/TDS	Automatic with b selectable from 2.4%/°C with 0.1 increments		
pH Calibration		Automatic 1 or 2 point calibration with 2 sets of memorized buffers (4.01, 7.01, 10.01 or 4.01, 6.86, 9.18)		

EC/TDS Calibration	1413 μS/cm	12.88 mS/cm	
EC/ I D3 Calibration	or 1382 ppm (CONV=0.5)	or 6.44 ppt (CONV=0.5)	
	or 1500 ppm (CONV=0.7)	or 9.02 ppt (CONV=0.7)	
TDS Conversion Factor	Selectable from 0.45 to 1.00 with 0.01 increments (default 0.50)		
Probe (included)	HI 1288 pH/EC/TDS/temperature with DIN connector and 1 m (3.3') cable		
Battery Type	(3) 1.2V AAA		
Battery Life	Approximately 200 hours of continuous use		
Auto-off	After 8 minutes of non-use		
Environment	0 to 50°C (32 to 122°F); RH max. 100%		
Dimensions	150 x 58 x 29 mm (5.9 x 2.8 x 1.1")		
Weight	205g (7.2 oz.)		

ORDERING INFORMATION

HI 991300 and **HI 991301** are supplied with HI 1288 pH/EC/TDS/temperature probe with DIN connector and 1 m (3.3') cable, calibration & cleaning solution sachets, (3)1.2V AAA batteries and instructions.

ELECTRODES

HI 1288 Pre-amplified

Pre-amplified pH/EC/TDS probe with built-in temperature sensor, DIN connector and

1 m (3.3') cable

SOLUTIONS

HI 7004L pH 4.01 buffer solution, 500 mL

HI 7006L	pH 6.86 buffer solution, 500 mL	
	F	
HI 7007L	II 7007L pH 7.01 buffer solution, 500 mL	
HI 7009L	7009L pH 9.01 buffer solution, 500 mL	
HI 7010L	010L pH 10.01 buffer solution, 500 mL	
HI 7030L	7030L 12880 μS/cm (μmho/cm) solution, 500 mL	
HI 7031L	1413 μS/cm (μmho/cm) solution, 500 mL	
HI 7032L	2L 1382 ppm (mg/L) solution, 500 mL	
HI 7038L	038L 6.44 ppt (g/L) solution, 500 mL	
HI 70442L	L 1500 ppm solution, 500 mL	
HI 70300L	Electrode storage solution, 500 mL	
HI 7061L	Electrode cleaning solution, 500 mL	



SPECIFICATIONS	UI 1500
Description	Spare electrode
Reference	Single, Ag/AgCl
Junction / Flow Rate	Cloth
Electrolyte	Gel
Max Pressure	1 bar
Range	pH: 0 to 13; EC T: 0 to 60°C (32 to 140°F)
Tip /Shape	Spheric (dia: 8.5 mm)
Temperature Sensor	Yes
Amplifier	Yes
Body Material	PVC
Connection/Cable	DIN/7-pole; 2 m (6.6')
Recommended Use	General purpose, water treatment, agriculture, boilers, cooling towers

